

















Ondervloerenmatrix Ondervloerplaten

ONDERVLOERPLATEN	Parketman 4 mm	Parketman 7 mm	Redupax	Redupax+	Soundkiller	SoundEx	Parpax	Redupanel	Accoustimax
Verpakkingseenheid	12,04 m ²	10,25 m ²	8,12 m ²	4,4 m ²	4,06 m ²	6,09 m ²	2,31 m ²	1,44 m ²	0,69 m ²
Kliklaminaat	○	○			-	○	X	X	X
Klikfineerparket	○	○	○		○	○	X	X	X
Lamelparket (verlijmd)	○	○	○	○		○	X	X	X
Kliklamelparket	○	○	○	○		○	X	X	X
Lamelplank 19/20 mm	○	○	○	○		○	X		X
Massieve plank 20 mm	○	○	○	○	○		X	X	X
Marmoleum click	○	○	○		○	○	X	X	X
Cork-o-Loc	○	○		○	○	○	X	X	X
Wood-o-Loc	○	○		○	○	○	X	X	X
Tapis 6 mm	X	X	X	X	X	X		X	
Bourgogne/tapis 9 mm	X	X	X	X	X	X	X		
2-laags tapis	X	X	X	X	X	X		X	X

Bij ondervloeren met vochtwerende folie wordt de schuimzijde op de dekvloer gelegd en de foliezijde naar boven. Bij gebruik van ondervloerplaten dient altijd eerst een vochtwerende folie te worden gelegd.

	Mogelijk
	Niet mogelijk
-	Onbekend
	TNO getest: +10 dB